

# Grease Pumps LAGG series

## Meeting all your grease lubricator needs

Full range of manual and air-operated grease pumps are designed to empty standard 18, 50 or 180 kg (39, 110 or 400 lb) grease drums. Can be connected directly on the greasing points, also suitable for centralised lubricating grease systems.

SKF grease pumps have a maximum pressure of 40 and 42 MPa (5 800 and 6 090 psi) respectively. Tested and approved for SKF greases. Easy to install and ready for use since pumps are supplied with all necessary items including 3 500 mm (137,8 in) of tubing.

- Full range; pumps available for 18, 50 or 180 kg (39, 110 or 400 lb) drums
- High pressure; maximum of 42 MPa (6 090 psi)
- Easy to install; all necessary items as well as 3 500 mm (137,8 in) of tubing are included
- Reliable; tested and approved for SKF greases
- Can be used in combination with SKF bearing packer VKN 550



### Ordering details

Designation	Description
LAGG 18M	Grease pump for 18 kg drums
LAGG 18AE	Mobile grease pump for 18 kg drums
LAGG 50AE	Grease pump for 50 kg drums
LAGG 180AE	Grease pump for 180 kg drums
LAGT 180	Trolley for drums up to 200 kg



Re-lubrication



## LAGG series

Designation	LAGG 18M	LAGG 18AE	LAGG 50AE	LAGG 180AE	LAGT 180
<b>Description</b>	Grease pump for 18 kg drums	Mobile grease pump for 18 kg drums	Grease pump for 50 kg drums	Grease pump for 180 kg drums	Trolley for drums up to 200 kg
<b>Pumping</b>	Manual	Air-pressure	Air-pressure	Air-pressure	n.a.
<b>Max. pressure</b>	50 MPa (7 250 psi)	42 MPa (6 090 psi)	42 MPa (6 090 psi)	42 MPa (6 090 psi)	n.a.
<b>SKF Drum</b>	18 kg (39.6 lb)	18 kg (39.6 lb)	50 kg (110 lb)	180 kg (396 lb)	180 kg (396 lb)
<b>Inner diameter</b>	265 – 285 mm (10.43 – 11.22 in)	265 – 285 mm (10.43 – 11.22 in)	350 – 385 mm (13.78 – 15.16 in)	550 – 590 mm (21.65 – 23.23 in)	n.a.
<b>Note</b>	Stationary	Mobile	Stationary	Stationary	Mobile
<b>Volume/stroke</b>	1,6 cc	–	–	–	–
<b>Volume/min.</b>	–	200 cc	200 cc	200 cc	–
<b>Suitable grease NLGI class</b>	000 – 2	0 – 2	0 – 2	0 – 2	–

# Grease Filler Pumps LAGF series

## High quantity grease packer

SKF Grease Filler Pumps are suitable for filling grease guns. Especially designed for use on grease gun 1077600 and LAGH 400. Tested and approved for SKF greases. Easy to install and ready for use. Available for standard SKF 18 and 50 kg (39 and 110 lb) drums.

- Quick filling: low pressure allows higher stroke volume
- Easy to install: all necessary items are included
- Reliable: tested and approved for all SKF greases
- Can be used in combination with SKF Bearing Packer VKN 550



### Ordering details

Designation	Description
LAGF 18	Grease filler pump for 18 kg drums
LAGF 50	Grease filler pump for 50 kg drums

## LAGF series

Designation	LAGF 18	LAGF 50
<b>Maximum pressure</b>	3 MPa (430 psi)	3 MPa (430 psi)
<b>Volume/stroke</b>	approx. 45 cm <sup>3</sup> (1.5 fl. oz.)	approx. 45 cm <sup>3</sup> (1.5 fl. oz.)
<b>Suitable drum dimensions:</b>		
– inside diameter	265 – 285 mm (10.4 – 11.2 in)	350 – 385 mm (13.8 – 15.2 in)
– maximum inside height	420 mm (16.5 in)	675 mm (26.6 in)
<b>Weight</b>	5 kg (11 lb)	7 kg (15 lb)

© SKF is a registered trademark of the SKF Group

© SKF Group 2009

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

MP/PDS LAGG EN • October 2009

[www.mapro.skf.com](http://www.mapro.skf.com) • [skf.com/mount](http://skf.com/mount) • [skf.com/lubrication](http://skf.com/lubrication)

