



Pinpoint accuracy combined with measurement versatility

SKF Tachometer TKRT 10

The SKF TKRT 10 is a fast and accurate tachometer utilizing laser or contact to measure rotational and linear speeds. Equipped with a laser and a range of contact adapters, it is a versatile instrument and suits many different applications.

- Wide speed measurement range: up to 99 999 r/min for laser measurement and 20 000 r/min using contact adapters.
- Measurement modes include; rotational speed, total revolutions, frequency, surface speed and length in both metric and imperial units.
- Laser can be used for safe and quick, non-contact rotational speed measurements at distances up to 0.5 m (20 in.).
- Large back-lit LCD display enables easy reading in almost all light conditions.
- Angular range of $\pm 45^\circ$ to target helps facilitate easy measuring.
- Up to 10 readings can be stored for later reference.
- Compact design; one-hand operated instrument.
- Supplied in carrying case for protection and portability.



Equipped with a laser and a range of contact adapters





The laser optical system allows easy and quick measurements at a safe distance from rotating machinery

Technical data

Designation	TKRT 10
Display	5 digit LCD backlit display
Displayed resolution	0,1 r/min up to 10 000 r/min, otherwise 1 r/min
Memory	10 readings memories
Low battery indicator	Yes
Auto switch off	After 15 seconds
Measurement	
Optical modes	r/min, hertz
Contact modes	r/min, metres, inches, yards, feet, per min, hertz
Count modes	total revs, metres, feet, yards
Sampling time	0,5 seconds (over 120 r/min)
Linear speed	0,2 to 1 500 metres/min (4 500 ft/min)
Optical measurement	
Rotational speed range	3 to 99 999 r/min
Accuracy	±0,05% of reading ±1 digit
Measuring distance	50 to 500 mm (1.9 to 19.7 in.)
Angle of operation	±45°
Laser sensor	1× built-in class 2 laser

Contact measurement	
Rotational speed range	2 to 20 000 r/min
Accuracy	±1% of reading ±1 digit
Contact adaptors	Included with conical tip, conical recess and wheel
Battery	1× 9 V alkaline type IEC 6F22
Operation time	12 hours continuous use
Additional power source	6 V DC charging port (charger not included)
Product dimensions	160 × 60 × 42 mm (6.3 × 2.4 × 1.7 in.)
Product weight	160 g (0.35 lbs)
Operating temperature	0 to 50 °C (32 to 122 °F)
Storage temperature	-10 to +50 °C (14 to 122 °F)
Relative humidity	10 to 90% RH non-condensing
IP rating	IP 40
Case contents	1× SKF Tachometer TKRT 10 1× set of 3× contact adaptors 1× 9 V battery 1× set of reflective tape 1× printed instructions for use

© SKF is a registered trademark of the SKF Group.

© SKF Group 2014

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 14153 EN · April 2014

