

LGMT 3

SKF General Purpose Industrial and Automotive Bearing Grease

SKF LGMT 3 is mineral oil based, lithium soap thickened grease. This premium quality, general purpose grease is suitable for a wide range of industrial and automotive applications requiring stiff grease.

- Excellent rust inhibiting properties
- High oxidation stability within its recommended temperature range

Typical applications:

- Bearings >100 mm (3.9 in.) shaft size
- Outer bearing ring rotation
- Vertical shaft applications
- Continuous high ambient temperatures >35 °C (95 °F)
- Propeller shafts
- Agricultural equipment
- Car, truck and trailer wheel bearings
- Large electric motors



Technical data

Designation	LGMT 3/(pack size)		
DIN 51825 code	K3K-30	Corrosion protection	
NLGI consistency class	3	Emcor: – standard ISO 11007	0–0
Soap type	Lithium	– water washout test	0–0
Colour	Amber	Water resistance	
Base oil type	Mineral	DIN 51 807/1,	
Operating temperature range	–30 to +120 °C (–20 to +250 °F)	3 hrs at 90 °C	2 max.
Dropping point DIN ISO 2176	>180 °C (>355 °F)	Oil separation	
Base oil viscosity		DIN 51 817,	
40 °C, mm ² /s	120–130	7 days at 40 °C, static, %	1–3
100 °C, mm ² /s	12	Lubrication ability	
Penetration DIN ISO 2137		R2F,	
60 strokes, 10 ⁻¹ mm	220–250	running test B at 120 °C	Pass
100 000 strokes, 10 ⁻¹ mm	280 max.	Copper corrosion	
Mechanical stability		DIN 51 811, 110 °C	2 max. at 130 °C (265 °F)
Roll stability, 50 hrs at 80 °C, 10 ⁻¹ mm	295 max.	Rolling bearing grease life	
V2F test	'M'	ROF test	1 000 min. at 130 °C (265 °F)
		L ₅₀ life at 10 000 r/min., hrs	
		Available pack sizes	420 ml cartridge 0,5, 1, 5, 18, 50, 180 kg



SKF lubricants offer major competitive advantages:

- Designed and tested to outperform under real conditions
- Product data include specific test results enabling a better selection
- Strict quality control of every production batch help ensure consistent performance
- Quality control allows SKF to offer a five-year shelf-life* from the date of production



Production processes and raw materials vastly influence grease properties and performance. It is virtually impossible to select or compare greases based only on their composition. Therefore, performance tests are needed to provide crucial information. In over 100 years, SKF has accrued vast knowledge about the interaction of lubricants, materials and surfaces.



This knowledge has led SKF, in many cases, to set industry standards in bearing lubricant testing. Emcor, ROF, ROF+, V2F, R2F and Bequiet are just some of the multiple tests developed by SKF to assess the performance of lubricants under bearing operating conditions. Many of them are widely used by lubricant manufacturers worldwide.

* SKF LGFP 2 food grade grease offers a two-year shelf-life from the date of production

© SKF is a registered trademark of the SKF Group.

© SKF Group 2011

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 12053 EN · July 2011

