

Why SKF?

Chains



SKF Chains are manufactured in state-of-the-art facilities. Tight quality controls are employed to assure product conformance to the ISO standards and the existing industrial standards mainly ANSI, BS, DIN and JIS. SKF Oil field chains are American Petroleum Institute (API) approved and each box carries the API monogram. SKF automotive chain meets the ISO/TS16949 Quality Assurance System technical specification. This specification aligns American (QS-9000), German (VDA6.1), French (EAQF) and the Italian (AVSQ) automotive quality system standards within the global automotive industry.

All SKF Chains have a normal operating temperature range of -20 to 150 °C. An exception is stainless steel chains with a range of -20 to 400 °C. For higher temperatures alternative lubrication should be applied. Please, also note that for temperatures over 200 °C and below -20 °C breaking load values are reduced.

Product features

- From the raw material to the finished product, our chain is superior by design: 100 % pre-stressing, 100 % pre-loading and running prior to packaging
- SKF uses a heavy pre-lubrication process to enable optimum storage life; all of SKF chain is fully wrapped in plastic prior to being boxed
- A very large range of plating is available: Dacromet, nickel, zinc and stainless steel
- SKF also supplies a full range of conveyor chain for every application

User benefits

- Enhance worker safety
- Improve hygiene
- Improve product quality
- Improve reliability
- Increase production
- Reduce downtime
- Reduce energy consumption
- Reduce maintenance costs
- Reduce need for maintenance
- Reduce operating costs
- Reduce waste
- Shorten delivery times

Common applications

- Coke oven
- Contiguous casting
- Conveyors
- Crushers
- Elevators
- First mill
- Plate mills
- Reheat furnaces
- Rolling mills
- Shrink packers

SKF Xtra roller chains - Standard



- Suitable for applications with higher shock loads and lower operating speeds
- 100 % pre-stressing, 100 % pre-loading and running prior to packaging
- Heavy pre-lubrication process to enable optimum storage life
- Fully wrapped in plastic prior to being boxed

SKF Xtra roller chains - Self-lubricating



- 100 % pre-stressing, 100 % pre-loading and running prior to packaging
- Heavy pre-lubrication process to enable optimum storage life
- Fully wrapped in plastic prior to being boxed

Roller chains - Standard



- 100 % pre-stressing, 100 % pre-loading and running prior to packaging
- Heavy pre-lubrication process to enable optimum storage life
- Fully wrapped in plastic prior to being boxed

Double pitch chains



- Economical choice for low speed, moderate load, and long centre distance applications
- 100 % pre-stressing, 100 % pre-loading and running prior to packaging
- Heavy pre-lubrication process to enable optimum storage life
- Fully wrapped in plastic prior to being boxed

© SKF is a registered trademark of the SKF Group.

© SKF Group 2009

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

August 2009

skf.com

